Type 1+2 AC surge protector - 1-pole

DS500E-400

- Type 1+2 unipolar AC surge protector
- Iimp : 50 kA on 10/350µs impulse
- Imax : 200 kA on 8/20µs impulse
- Internal disconnecctions, status indicator and remote signaling
- IEC 61643-11 and EN 61643-11





V: High-energy varistor
Ft: Thermal fuse
C: Remote signal contact
t°: Thermal disconnection system
MI: Disconnection indicator

Electrical Characteristics		
SPD type	IEC	1+2
Network		230/400V
Max. AC operating voltage	Uc	440 Vac
Max. load current *if series connection*	IL	100 A
Temporary Over Voltage (TOV) Characteristics - 5 sec. *Without disconnection*	UT	580 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn *Without disconnection or with safety disconnection*	UT	770 Vac disconnection
Residual Current *Leakage current to Ground*	Ipe	< 3 mA
Follow current	If	None
Nominal discharge current *15 x 8/20 µs impulses*	In	50 kA
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	200 kA
Impulse current by pole *max. withstand 10/350µs by pole*	Iimp	50 kA
Specific energy by pole *max. withstand 10/350 µs*	W/R	625 kJ/ohm
Connection mode(s)		L/N and L/PE
Protection level *@ In (8/20µs)*	Up	2.2 kV
Admissible short-circuit current	Isccr	50 000 A
Mechanical Characteristics		
Technology		MOV
Connection to Network		By screw terminals: 6-35mm²
Format		1-pole modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator
Remote signaling of disconnection		Output on changeover contact
Dimensions		See diagram
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses Type gG - 500 A
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11
Certification		
Part number		
3964		