




CITEL

'Quarter wave' coaxial protector

PRC822S-N/MF



- 'Quarter wave' coaxial protector type N
- Frequency : 800-2200 MHz
- Low insertion loss
- I_{max} > 50 kA
- Maintenance free
- Bi-directional
- IP65




Electrical Characteristics		
Frequency range	f	800-2200 MHz
Insertion loss		< 0.1 dB
Return loss		> 20 dB
Impedance		50 ohms
VSWR		<1.1:1
Max. load current @25°C	IL	10 A
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	50 kA
Nominal discharge current C2 Category	I _n	25 kA
Protection mode(s)		Common mode
Protection level @1kV/µs (C3)	Up	30 V
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	25 kA
Max Power @f max.		867 W
Max Power @f mini.		1437 W
PIM 3rd order (2x20W)		< -160 dBc
DC Pass		No
Mechanical Characteristics		
Technology		Quarter Wave
Connection to Network		Connector N Male/Female
Mounting		Connector
Housing material		Brass/Surface plating: Cu Zn Sn
Operating temperature	Tu	-40/+85°C
Protection rating		IP65
Failsafe mode		Without
Dimensions		See diagram
Contacts		Bronze/Surface Au-Ag
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497E
RohS compliance		Yes
Part number		
61003		



CITEL

PRC822S-N/MF





CITEL

PRC822S-N/MF

